

KÖSTER Bikuplan® Butyl Fix-Tape Fleece

- Industry classification "Bikuplan" registered at the German patent office, 3955 6699

Cold self-adhesive, fleece-laminated butyl waterproofing tape for upper connections of KÖSTER Bikuplan® KSK membranes

Features

KÖSTER Bikuplan® Butyl Fix-Tape Fleece is fleece-laminated waterproofing tape on butyl / rubber basis. It is cold self-adhesive, 1.5 mm thick with a separating backing paper on the bottom side. The material can be applied directly from the roll, it is highly tear resistant, immediately waterproof and it can be covered with plaster due to its fleece-laminated upper side. Priming before application of the KÖSTER Bikuplan® Butyl Fix-Tape Fleece is not necessary.

Technical data

Material	Butyl / Rubber
Width	15 cm
Thickness	1.5 mm
Temperature resistance	- 25 °C to + 80 °C
Application temperature	+ 5 °C to + 30 °C
µ-value	approx. 135.000
Sd-value	approx. 203

Field of application

KÖSTER Bikuplan® Butyl Fix-Tape Fleece is designed for the safe upper connection of KÖSTER Bikuplan® KSK membranes on solid, clean, dry, dust- and oil-free substrates.

Application

After waterproofing with KÖSTER Bikuplan® KSK membranes, KÖSTER Bikuplan® Butyl Fix-Tape Fleece is attached on the upper end of the waterproofing whereby the tape is attached so that half of it covers the membrane and the other half covers the substrate; thus a connection is built which can be plastered. Prior to the application, the protective backing paper on the bottom side of the tape has to be removed.

Due to the laminated fleece on the upper side of the tape, it can be covered with plaster, e. g. in base areas.

Cleaning of tools

Clean soiled sticky cutting tools with KÖSTER Bitumen Remover.

Packaging

10 m roll, width of rolls: 15 cm

Storage

Store the material in a dry place at temperatures between + 5 °C and + 30 °C; it can be stored for approx. 1 year.

Technical guidelines cited

KÖSTER Bitumen Remover	Art. No. 9.03
KÖSTER Bikuplan® KSK membranes	Product group 10

The accurate and thereby effective and successful installation of our products is not subject to our control. The guarantee can therefore only be applied to the quality of our products within the scope of our terms and conditions, not, however, for their effective and successful installation. These guidelines replace all previous ones.